# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

#### Supplier's name or trade mark: Ubbink

Supplier's address: Produktmanagement, Berenkoog 87, 1822 Alkmaar, NL

#### Model identifier: 1312124

### Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	others				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

Parameter		Value	Parameter	Value		
General product parameters:						
•.	nption in on- 100 h), rounded st integer	3	Energy efficiency class	G		
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	230 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	10 000		
On-mode p expressed in W	oower (P <sub>on</sub> ),	3,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
for CLS, expres	dby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	74		
Outer dimensions	Height	100	Spectral power	See image		
	Width	300	distribution in the	in last page		
without	Depth	175		Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	lf yes, equivalent power (W)	-			
		Chromaticity	0,286			
		coordinates (x and y)	0,278			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	74	Survival factor	1,00			
the lumen maintenance factor	0,95					
(a)						

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

## Spectroradiometric Parameters

